

HOT SPOT<sup>®</sup> COLLECTION

# TX



2

People

11

Jets

Open

Seating

115 or 230

Voltage

6' x 6' x 29"

Dimensions

FROG<sup>®</sup> In-Line Cartridge Ready

Water Care

# TX




TX spa shown with Alpine White shell, and Storm cabinet.

**Shell Colors**



**Cabinet Colors**



**Cover Colors**



<b>Seating Capacity</b>	2 people	<b>Control System</b>	IQ 2020® 115 V / 15 amp,** 60 Hz (Includes G.F.C.I. protected power cord) or 115 V / 30 amp*** or 230 V / 50 amp*** 60 Hz
<b>Dimensions</b>	6' x 6' x 29" / 1.83 m x 1.83 m x 0.74 m	<b>Lighting – Interior</b>	4 multi-color LED points of light, dimmable
<b>Water Capacity</b>	190 gallons / 720 liters	<b>Heater</b>	No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
<b>Weight</b>	635 lbs. / 290 kg dry; 2,570 lbs. / 1,165 kg filled*	<b>Energy Efficiency</b>	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
<b>Jets (All with stainless steel trim)</b>	11 total <ul style="list-style-type: none"> <li>• 1 Moto-Massage® jet</li> <li>• 1 Directional Hydromassage jet</li> <li>• 1 Rotary Hydromassage jet</li> <li>• 8 Directional Precision® jets</li> </ul>	<b>Effective Filtration Area</b>	30 sq. ft., top loading
<b>Jet Pump</b>	Wavemaster® 4200; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque	<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 1.5 lb. density foam core
<b>Circulation Pump (Optional)</b>	SilentFlo® 5000	<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, or UpRite®
<b>Floor Drain</b>	Included	<b>Steps (Optional)</b>	Everwood® - Almond, Havana, and Storm Polymer - Ash
<b>Water Care System</b>	FROG® In-Line Cartridge Ready		

Actual colors and products may vary from print representation. See dealer to verify. \*Includes water and 2 adults weighing 175 lbs. each. \*\*Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. \*\*\* G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.